



Project/Job Name: _____
 Location: _____
 Fixture Type: _____
 Notes: _____

S21297 - 4 Watt CA10 LED; Clear; Candelabra base; 90 CRI; 3000K; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	4W
Volts:	120V
Lumens:	350L
CRI:	90+
Rg Value :	53
CCT (Kelvins):	3000K - Soft White
Beam Spread :	300
Hours Rated:	15000
Dimmable:	Yes-Dimmable - 120V only
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	40W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	0.75
Light Source:	LED Filament
Voltage Type:	AC Only
Warranty:	3 Year Limited

PACKAGING

Each UPC:	045923206122
Each Quantity:	1
Each Dimensions:	1.65 x 1.65 x 4.96

PHYSICAL

Base:	Candelabra
Shape:	CA10
Finish:	Clear
Dimensions (In.):	MOL: 4.72 - MOD: 1.38
Weight (Lbs.):	0.035
Material:	Glass / Nickel Plated Aluminum
Housing Color:	None

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NOM-030-ENER-2016!NTEC22ENM004056
NOM Expiration Date:	4/25/2024
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

DIMMER COMPATIBILITY

Leviton 6672

Leviton 6674

Satco 86/103

Lutron AYCL-153P

Lutron CTRP-253P

Eaton DALo6P-C2

Leviton DDMX1

Leviton DG6HD

Leviton DH6HD

Leviton DL6HD

Leviton DSLo6

Leviton DSLo6-1LZ

Leviton DSM1o

Eaton DULo6P-C2

Lutron DVCL-153P

Lutron DVRP-253P

Leviton DW6HD

Leviton DZ6HD

Leviton IPLo6

Lutron LECL-153PH

Lutron MA-PRO

Lutron MACL-153M

Lutron MSCL-OP153M

Lutron NTCL-250

Lutron NTRP-250

Lutron PD-1oWX

Lutron	PD-6WCL
Lutron	RCL-153PNL
Eaton	RF9640-ND
Legrand	RHCL450PTC
Leviton	RNL06-10Z
Lutron	RRD-6CL
Lutron	RRD-PRO
Satco	S11268
Eaton	SUF7
Leviton	TSL06
Leviton	TSM10
Eaton	VSUL06D