





FEATURES & BENEFITS				
10 YEAR WARRANTY (casting only)	SUITABLE FOR LOW PRESSURE	35 MM TAP HOLE REQUIRED	EASY FIT FLEXI TAILS	
CERAMIC DISC CARTRIDGE	360 DEGREE SWIVEL SPOUT	DUAL LEVER	AERATOR SPOUT	

SPECIFICATION		
Finish	Chrome Only	
Body	Brass	
Fitting	Easy fit	
Connection	Flexible connection hoses	

DAK PRESSURE	
Min Pressure	0.2
Max Pressure	6.0

DAD DDECCLIDE

FLOW RATES			
0.2	0.5	1	3
4.5	6.5	9.4	18.6

All pressures are in bar.

Dimensions supplied are nominal and subject to tolerance.

Inclusion of aerator (if supplied) or restrictors (supplied separately) will affect flow rate result.

Performance details are based on trails under test conditions and are for guidance only.

The manufacturer reserves the right to change product specification without prior notice.

PACKAGE DIMENSIONS	
andust Mainht	1 11/

Product Weight	1.1KG
Packed Weight	1.35KG
Box Dimensions	390x200x60mm

CARE & MAINTENANCE

Reginox recommends cleaning your tap regularly with non-abrasive cleaners. Warm, soapy water would be best.